

# Material Safety Data Sheet

May be used to comply with OSHA's Hazard Communication Standard 29 CFR 1910.1200. Standard must be consulted for specific requirements.



## U.S. Department of Labor

Occupational Safety and Health Administration  
(Non-Mandatory Form)  
Form Approved  
OMB No. 1218-0072

IDENTITY ( As Used on Label and List)

KT WHITE PAINT

Note: Blank spaces are not permitted. If any item is not applicable or no information is available, the space must be marked to indicate that.

### Section I

<b>Manufacturer's Name</b>	BROCK SUPPLY CO.	<b>Emergency Telephone Number</b>	INFOTRAC 1-800-535-5053
<b>Address</b>	2150 E. RIO SALADO PKWY. P.O. BOX 1000 TEMPE, AZ 85280-1000	<b>Telephone Number for Informatic</b>	(480) 968-2222
		<b>Date Prepared</b>	19-Aug-03
		<b>Signature of Preparer (optional)</b>	

### Section II - Hazardous Ingredients/Identity Information

Hazardous Components (Specific Chemical Identity; Common Name(s))	OSHA PEL	ACGIH TLV/stel	Other Limits Recommended	% (optional)
XYLENE, MIXED ISOMERS	100 PPM	150 PPM		
TOLUENE	200 PPM	150 PPM (SKIN)		
ISOPROYL ALCOHOL	400 PPM	500 PPM		
METHYL ISOBUTYL KETONE	100 PPM	75 PPM		
PROPYLENE GLYCOL METHYL ETHER ACETATE	NE	NE	LD50 ORAL (RAT) 8.5 g/kg	
ACETONE	750 PPM	750 PPM		
ETHYL BENZENE	100 PPM	25 PPM		
C.I. PIGMENT ORANGE 5	NE	NE	LD50 ORAL (RAT) 3500 mg/kg	
TITANIUM DIOXIDE	10 mg/cu	10 mg/cu (TWA)		

THIS SUBSTANCE IS CLASSIFIED AS A HAZARDOUS AIR POLLUTANT.

THIS PRODUCT CONTAINS 1 OR MORE REPORTED OR SUSPECTED CARCINOGENS, WHICH ARE NOTED.

THIS PRODUCT CONTAINS PIGMENTS WHICH MAY BECOME A DUST NUISANCE WHEN REMOVED BY ABRASIVE

BLASTING, SANDING OR GRINDING.

THIS PRODUCT CONTAINS 1 OR MORE REPORTED OR SUSPECTED REPRODUCTIVE TOXINS

### Section III - Physical/Chemical Characteristics

<b>Boiling Point</b>	133° F - 302° F	<b>Specific Gravity (H2O - 1)</b>	1.046
<b>Vapor Pressure (mm Hg)</b>		<b>Melting Point</b>	
<b>Vapor Density (AIR - 1)</b>	HEAVIER THAN AIR	<b>Evaporation Rate (Butyl Acetate - 1)</b>	5.7
<b>Solubility in Water</b>		<b>Material VOC</b>	4.836 LBS / GAL
<b>Appearance</b>	WHITE LIQUID		

### Section IV - Fire and Explosion Hazard Data

<b>Flash Point (Method Used)</b>	46° F	<b>Flammable Limits</b>	UNKNOWN	<b>LEL</b>	<b>UEL</b>
<b>Extinguishing Media</b>	WATER SPRAY, DRY CHEMICAL, CO2, ALCOHOL FOAM				
<b>Special Fire Fighting</b>	WEAR SELF-CONTAINED BREATHING APARATUS AND PROTECTIVE CLOTHING & EQUIP. USE WATER				
<b>Procedures:</b>	WITH CAUTION. WATER MAY BE USED TO COOL FIRE EXPOSED AREAS. MAY BE INEFFECTIVE ON FIRE.				
<b>Unusual Fire &amp; Explosion Hazards</b>	VAPORS MAY CAUSE A FLASH FIRE. MAY TRAVEL LONG DISTANCE TO SOURCE OF IGNITION.				

Unstable	Conditions to Avoid		
Stable	X	HIGH TEMPERATURES	
<b>Incompatibility (Materials to Avoid)</b>		CAN REACT VIOLENTLY WITH OXIDIZING AGENTS AND STRONG ACIDS	
<b>Hazardous Decomposition or Byproducts</b>		CARBON DIOXIDE CARBON MONOXIDE	
Hazardous Polymerization will not occur.			
<b>Section VI - Health Hazard Data</b>			
<b>Route (s) of Entry:</b>	<b>Inhalation?</b>	<b>Skin?</b>	<b>Ingestion?</b>
	Y	Y	Y
<b>Health Hazards (Acute and Chronic)</b>		CAUSES EYE IRRITATION. PROLONGED OR REPEATED SKIN CONTACT MAY CAUSE DRYING, CRACKING OR IRRITATION. HIGH VAPOR CONCENTRATION MAY CAUSE DROWSINESS AND IRRITATION OF EYES OR RESPIRATORY TRACT.	
SWALLOWING SMALL AMOUNTS OF THE MATERIAL DURING HANDLING IS NOT LIKELY TO CAUSE HARMFUL EFFECTS. LARGE AMOUNTS MAY BE HARMFUL. MAY AGGRAVATE ANY PREEXISTING RESPIRATORY OR SKIN CONDITION.			
<b>Carcinogenicity:</b>	<b>NTP?</b>	<b>IARC Monographs?</b>	<b>OSHA Regulated?</b>
	N	N	Y
<b>EMERGENCY FIRST AID PROCEDURES:</b>	EYES - FLUSH WITH WARM WATER FOR AT LEAST 15 MINUTES AND GET MEDICAL ATTENTION. SKIN - REMOVE FROM SKIN WITH SOAP & WATER. REMOVE DRENCHED CLOTHING. IF IRRITATION OCCURS, CONSULT A PHYSICIAN. INHALATION - REMOVE TO FRESH AIR. IF NECESSARY, RESTORE BREATHING. CONTACT PHYSICIAN. INGESTION - SEEK MEDICAL ADVICE.		
<b>Section VII - Precautions for Safe Handling and Use</b>		KEEP AWAY FROM HEAT, SPARKS AND FLAME. USE WITH ADEQUATE VENTILATION. KEEP CONTAINER TIGHTLY CLOSED.	
<b>Steps to be taken in Case Material is Released or Spilled</b>			
<b>Waste Disposal Method</b>	DISPOSAL SUBJECT TO NATIONAL, STATE AND LOCAL LAWS. MIX WITH COMPATIBLE CHEMICAL AND INCINERATE. EMPTIED CONTAINERS RETAIN PRODUCT RESIDUE. DO NOT CUT, DRILL, GRIND OR WELD ON THIS CONTAINER.		
<b>Section VIII - Control Measures</b>		GOOD GENERAL VENTILATION SHOULD BE USED. IF PERSONAL EXPOSURE CANNOT BE CONTROLLED BELOW APPLICABLE LIMITS BY VENTILATION, WEAR A PROPERLY FITTED ORGANIC RESPIRATOR APPROVED BY NIOSH.	
<b>Respiratory Protection (Specify Type)</b>			
<b>Ventilation</b>	<b>Local Exhaust</b>		
<b>GLOVES-</b> IF PROLONGED OR REPEATED SKIN CONTACT OCCURS	<b>Eye Protection-</b>		USE SAFETY EYEWEAR W/ SPLASHGUARDS
<b>Other Protective Clothing or Equipment</b>			
<b>Work/Hygienic Practices</b>			