

Material Safety Data Sheet

Section 1 Product and Company Identification

Product Name: FAST DRY PAINTSTIK
MSDS #: 116 **Date Prepared:** January 18, 1995
Revision #: 1.3 **Date Revised:** June 14, 2001

Manufacturer: | **Supplier/Importer:**

LA-CO INDUSTRIES, Inc. *Markal* Co. |

1201 Pratt Blvd. |

Elk Grove Village, IL, USA |

60007-5746 |

Information Telephone: 847-956-7600 |

Emergency Telephone: Call CHEMTREC

USA 800-424-9300

International (Call Collect) 1-703-527-3887

Chemical Formula: Mixture |

CAS No.: Not Applicable. **Synonyms:** Not Applicable.

Derivation: Not Applicable.

General Use: Paint crayon for general purpose marking.

Section 2 Composition/Information on Ingredients

<u>Ingredient</u>	<u>CAS No.</u>	<u>%</u>
Dipropylene Glycol Monomethyl Ether ^{3,4,5,6} ACGIH: TWA = 100ppm, STEL = 150ppm OSHA: TWA = 100ppm	34590-94-8	20
Hydrotreated Kerosene Acute oral LD50 (rat) >5g/kg Acute dermal LD50 (rabbit) >3.16g/kg	64742-47-8	5
Carbon Black ^{3,4,5,6} (Black Paintstik only) ACGIH: TWA = 3.5 mg/kg OSHA: TWA = 3.5 mg/kg	1333-86-4	3

(For Section 2 footnotes: See Section 15)

Section 3 Hazards Identification

EMERGENCY OVERVIEW: CAUTION: EYE IRRITANT. CONTAINS GLYCOL ETHER SOLVENT. Avoid eye contact - flush thoroughly with water, call physician. May be harmful if swallowed. KEEP OUT OF REACH OF CHILDREN.

POTENTIAL HEALTH EFFECTS:

Primary Entry Routes: Eyes, Skin, Inhalation

Acute Effects

Eyes: Vapors and direct contact can cause irritation.

Skin: Can cause drying of skin.